



TÜVRheinland®
Precisely Right.

ISO 9001



ZX-VICTORY

Your Partner for Gas Cylinder & Valve

DISPOSABLE - ALUMINUM



ISO 11118



DOT 39

Material: • AA6061-T6/AA3003

Specification: • ISO 11118 designed, TPED approval
• DOT 39 designed, DOT approval

Volume: • min 0.1L-max 1.5L (ISO 11118)
• 1.72L (DOT 39)

Valve Outlet: • M10x1, M11x1, M12x1 (ISO 11118)
• 5/8-18 UNF (DOT 39)
• other threads available

Finish: • brushed (standard finish)

Graphic: • custom shrink sleeve/label

ISO 11118 SPECIFICATIONS								
				DIA: 60/70/74mm			MIN 0.1L-MAX 1.5L	
WATER VOLUME	SERVICE PRESSURE	TEST PRESSURE	CO2 CAPACITY	DIAMETER	LENGTH	CYLINDER WEIGHT	MATERIAL	CERTIFICATION
liters	bar	bar	gr	mm	mm	kgs		
0.3	120	180	190	60	165	0.28	AA6061-T6	ISO 11118 Standard, TPED Approval
0.4	120	180	250	60	208	0.34	AA6061-T6	
0.6	110	165	380	70	240	0.46	AA6061-T6	
0.8	110	165	500	70	300	0.57	AA6061-T6	
0.95	110	165	600	70	350	0.65	AA6061-T6	
0.95	110	165	600	74	305	0.64	AA6061-T6	ISO 11118 Standard, DOT Approval
0.95	120	180	600	74	310	0.73	AA6061-T6	
1.0	120	180	630	74	324	0.77	AA6061-T6	
1.2	120	180	760	74	379	0.87	AA6061-T6	
Custom dimension/thread/finish available upon request								

DOT 39 SPECIFICATIONS								
WATER VOLUME	SERVICE PRESSURE	TEST PRESSURE	O2	DIAMETER	LENGTH	CYLINDER WEIGHT	MATERIAL	CERTIFICATION
liters	psi	psi	liters	mm	mm	kgs		
1.72	500	625	58	88.9	346	0.67	AA3003	DOT 39 Standard, DOT Approval
Custom dimension/thread/finish available upon request								

NingBo ZhengXin Pressure Vessel Co.,Ltd
 NingBo ZhengXin Fire-Fighting Equipment Co.,Ltd
 www.zxhpgas.com No.1 JinHuDong RD,
 info@zxhpgas.com YuYao 315466,
 tel. +86 21 5041 0838 Zhejiang CHINA