



**TÜVRheinland®**  
Precisely Right.

**ISO 9001**



**ZX-VICTORY**

Your Partner for Gas Cylinder & Valve

DISPOSABLE - STEEL



ISO 11118



DOT 39



**Material:** • Mild Steel Q235B/Q335B/DC04

**Specification:** • ISO 11118 designed, TPED approval  
• DOT 39 designed, DOT approval

**Service Pressure:** • 110bar/120bar/150bar/1600psi

**Volume:** • Min 0.3L-Max 6.7L

**Valve Outlet:** • M10x1, M11x1, M12x1  
• other threads available

**Finish:** • powder coated (standard finish)

**Graphic:** • custom shrink sleeve/label

**Accessories:** • plastic base/handle/nozzle

ISO 11118 SPECIFICATIONS								
DIA: 70/80/100/118/127mm							MIN 0.3L-MAX 6.7L	
WATER VOLUME	N2O CAPACITY	SERVICE PRESSURE	TEST PRESSURE	DIAMETER	LENGTH	CYLINDER WEIGHT	MATERIAL	CERTIFICATION
liters	gr	bar	bar	mm	mm	kgs		
0.95	580	110	165	70	305	1.43	Q235B	ISO 11118 Standard, TPED Approval
1.0	615	110	165	70	321	1.49	Q235B	
1.1	640	110	165	70	351	1.62	Q235B	
1.2	740	110	165	100	200	1.47	Q355B	
1.8	800	110	165	100	284	1.97	Q355B	
2.0	1000	110	165	100	313	2.14	Q355B	
2.2	1100	110	165	100	341	2.31	Q355B	
3.3	2000	110	165	118	365	3.48	Q355B	

DOT 39 SPECIFICATIONS								
WATER VOLUME	N2O CAPACITY	SERVICE PRESSURE	TEST PRESSURE	DIAMETER	LENGTH	CYLINDER WEIGHT	MATERIAL	CERTIFICATION
liters	gr	psi	psi	mm	mm	kgs		
0.95	640	1600	2000	80	235	1.10	DC04	DOT 39 Standard, DOT Approval

Custom dimension/thread/finish available upon request

NingBo ZhengXin Pressure Vessel Co.,Ltd  
 NingBo ZhengXin Fire-Fighting Equipment Co.,Ltd  
 www.zxhpgas.com No.1 JinHuDong RD,  
 info@zxhpgas.com YuYao 315466,  
 tel. +86 21 5041 0838 Zhejiang CHINA